

VECTOR FIELD ViSUALiZATiON

Course Notes

Roger A. Crawfis

Lawrence Livermore National Laboratory


June 1995

Outline

- **Advection Techniques**
 - Advection algorithms and issues
 - Streamlines, pathline and streaklines
 - Particle systems
 - Ribbons and tubes
 - Stream surfaces
 - Streamballs
 - Flow volumes
- **Global Techniques**
 - Hedgehogs
 - Vector Filter Kernel for Volume Rendering
 - Line Integral Convolution (LIC)
 - Line Bundles
 - Textured Splats
- **Classification Techniques**
 - Critical point determination
 - Vortex core representations
 - Skin-friction representation
- **Summary / Comparisons**


Advection Techniques

- Basic Theory
- Integration Algorithms
- Vector Field Domain
- Time-varying Issues




Streamlines, Pathlines, Streaklines


- Streamlines



Pathlines



Streaklines



Streamlines

- Many streamlines can give an overall feel for the vector field.





Image courtesy of Vee Hirsch, NASA Ames


Particle Systems

- Reeves introduced particle systems for representing fuzzy objects such as waterfalls, grass and fire.
- van Wijk uses particles with motion blur, depth of field and hidden particles to animate particles on stream surfaces.
- Max constrains particles to be within a tolerance of a contour surface.



Particle Systems — Max

- Max's particles are rendered using a small texture mapped dot that is stretch in the flow direction.
- If all of the dots are the same color, no sorting is required.
- New particles fade in as they approach the surface and fade out as they depart.



Ribbons and Tubes

- Ribbons can be constructed using 2 or 3 particle advections per segment.
- Ribbons can also be calculated using the curl of the vector field about a streamline.
- Ribbons and Tubes provided an added depth cue with lighting.
- Schroeder describes a stream polygon for multivariate visualization





Image courtesy of H. Pagendarm, DLR.


Time lines

- Timelines or time surfaces can show the evolution of a flow.



Stream Surface — Explicit

- **Stream Surfaces can be generated explicitly as outlined by Hulquist:**
 - Start with segmented curve
 - Advect each vertex forward
 - If adjacent vertices diverge, add new vertices
 - If adjacent vertices converge, merge the vertices
 - If too much divergence, let the surface split and form a tear.




Stream Surface — Implicit

- **Stream Surfaces can also be generated implicitly as outlined by van Wijk:**
- **Place a continuous function on the inlet's of a flow simulation.**
- **For each sample point, trace backwards to inlet**
- **The value at the inlet intersected with the streamline is used to generate a function $f(x,y,z)$**
- **Take isocontour of the function $f(x,y,z)$ to get a stream surface.**

Streamballs — Overview


- Based on meta-balls
- Implicitly generated surfaces
- Easily split and merge
- Computationally expensive
- Need fine meshing to do accurate isocontouring



Images courtesy of Hans Hagen. Reprinted from Proceedings Visualization '94.

StreamBalls — Specifics


- Basic idea is to create a continuous function $f(x,y,z)$.
- And take isocontours of this function.
- Use metaballs to generate this function.
- Metaballs were developed separately by Nishimura, Blinn, and Wyvill.
- They were further refined by Bloomenthal and Shoemake.
- Treat particles as metaballs or use a timeline curve.



Images courtesy of Hans Hagen. Reprinted
from Proceedings Visualization '94.

Streamballs — Specifics


- A rake of particles will start out as a stream surface.
- Other variables can easily be mapped to the surface's color and texture.
- Other variables can control the shape of the resulting contour surface.



Images courtesy of Hans Hagen. Reprinted from Proceedings Visualization '94.


Flow Volumes — Overview

- Construction of the flow volume
- Volume rendering and compressibility
- Advection through various mesh topologies
- Puffs and colored flow volumes
- Unsteady Flow Volumes




Flow Volume — Specifics

- Seed polygon (square) is used as smoke generator.
- Constrained such that center is perpendicular to flow.
- Square can be subdivided into a finer mesh.
- Like explicit stream surfaces, the volume is adaptively subdivided in areas of high divergence.
- There is no merging.





Flow Volumes — Specifics

- Volume rendering is fast due to:
 - Hardware assisted tetrahedra rendering
 - Constant colored smoke doesn't require sorting.
- Compressibility option highlights converging areas.
- Opacity is inversely proportional to the tetrahedra's volume.




Flow Volumes — Specifics

- Object-oriented framework allows the flow field to be defined on many mesh topologies.
- Currently defined for regular, rectilinear, curvilinear, multigrid and unsteady meshes.




Flow Volumes — Specifics

- Can simulate puffing smoke
- Flow volume can be color-coded to represent other fields.




Flow Volumes — Unsteady

- Recently extended to unsteady flows for all mesh types.
- Complex twisting needs to be handled well.





Global Techniques

- Hedgehogs
- Vector Filter
- Line Integral Convolution
- Spot Noise
- Line Bundles
- Textured Splats




Hedgehogs

- Useful for 2D slices
- Regular patterns can be misleading
- Too much clutter for 3D fields




Vector Kernel for Volume Rendering

- Sampled space in back-to-front order
- Image reconstruction kernel for a scalar field
- Anti-aliased line for a vector field



Vector Kernel

- Build up compositing layers in back-to-front order.
- For each layer, pass vector kernel over entire image plane.
- This kernel moves in a discrete and jittered path left to right and top to bottom.
- The kernel samples the scalar and vector fields.
- The vector field uses a weighted probability of drawing an antialiased line across the kernel.
- The line is oriented in the vector field direction.
- The probability is proportional to the vector magnitude.



Line Integral Convolution (LIC)

- Given: vector field and texture image
- Output: colored field correlated in the flow direction
- Texture image is normally white noise.




Image courtesy of Brian Cabral.

LIC — Specifics

- Assume input texture, vector and output images are all the same resolution.
- For each output pixel/voxel, generate a streamline both forwards and backwards of a fixed length.
- Integrate the intensity that the streamline passes through.




Image courtesy of Brian Cabral.

LIC — Specific

- A convolution integral with a windowing function can be used rather than the raw integration (a weighting function).
- A phase shifted Hanning window allows a smooth and continuous animation.




Image courtesy of Brian Cabral.

LIC — Specifics

- LIC is dimension independent and works equally well for 3D.
- The resulting high-resolution colored volume resulting from LIC must then be rendered.
- The kernel integration can also be costly.





Image courtesy of Brian Cabral.


Line Bundles or Line Splats

- Basic Idea: Create an anisotropic texture.
- A set of lines (a line bundle) is created such that:
 - Color of each line is jittered
 - Center of each line is randomly placed within unit cube.
 - All lines are oriented in the same direction.
- Very Fast



Line Bundles — Specifics


- A line bundle is drawn for each data point in back-to-front order (much like splatting).
- The line bundle is oriented in the direction of the flow at that point.
- The line bundles are allowed to overlap to yield a smooth texture.
- The composited set of line bundles produces an image representing an anisotropic volume density cloud.



Textured Splats


- **Basic Idea:**

- Map reconstruction footprint from splatting to a 2D textured square.
- Add anisotropic “scratches” to the texture.
- Splat textures oriented in the projected direction of the flow.
- The back-to-front compositing yields a volume rendering with vector icons embedded.




Textured Splats — Specifics

- A set of textures can be constructed for animation.
- The vector icons are cyclically shifted before being windowed.




Textured Splats — Specifics

- The textures can be used without the scalar reconstruction to construct an anisotropic volume.



Textured Splats — Specifics

- The vector icons can be stretched in the vector direction to construct a brushed-like volume.



Classification of Critical Points

- Determine points where velocity vanishes - the critical points.
- Categorize these points based on surrounding flow: source, sink, saddle, spiral saddle, etc.
- Represent different types of critical points with different icons
- Connect the critical points for a global view of the field

Critical Points

- The eigenvalues of the matrix of partial derivatives of the velocity determine the type of a critical point.




Image courtesy of Al Globus, NASA

Vortex Cores

- Determining and representing vortex cores has been explored by several researchers




Images courtesy of David Banks.
Reprinted from Proceedings Visualization '94.




Skin-Friction Lines

- Skin-friction lines and other features can also be identified.



Images courtesy of H. Pagendarm, DLR.



Summary

- Cost of integration for thousands of points can be expensive
- For global methods using volume rendering, sorting can be expensive for non-regular data sets.
- Streamlines, etc. give a more quantitative representation, though only locally.
- Texture methods give a more global view, though qualitative.
- Solution: use texture techniques to determine areas to investigate further with advection techniques.
- Combine texture methods with classification methods.

Further Reading

- [1] Banks, D.C. and B.A. Singer. Vortex Tubes in Turbulent Flows: Identification, Representation, Reconstruction. in Visualization '94. 1994. Washington, D.C.: IEEE Computer Society Press.
- [2] Becker, B.G., D.A. Lane, and N.L. Max. Unsteady Flow Volumes. in Visualization '95. 1995. Atlanta, Georgia: IEEE Computer Society Press.
- [3] Brill, M., et al. Streamball Techniques for Flow Visualization. in Visualization '94. 1994. Washington, D.C.: IEEE Computer Society Press.
- [4] Cabral, B. and C. Leedom. Imaging Vector Fields Using Line Integral Convolution. in Computer Graphics. August 1993.
- [5] Crawfis, R. and N. Max. Direct Volume Visualization of Three-Dimensional Vector Fields. in Proceedings of the 1992 Workshop on Volume Visualization. 1992. New York: ACM SIGGRAPH.
- [6] Crawfis, R. and N. Max. Texture Splats for 3D Vector and Scalar Field Visualization. in Visualization '93. 1993. Los Alamitos, CA: IEEE Computer Society Press.
- [7] Crawfis, R., N. Max, and B. Becker, Vector Field Visualization. Computer Graphics and Applications, 1994. 14(5): p. 50-56.
- [8] Forssell, L.K. Visualizing Flow Over Curvilinear Grid Surfaces Using Line Integral Convolution. in Visualization '94. 1994. Washington, D.C.: IEEE Computer Society Press.

Further Reading

- [9] Globus, A., C. Levit, and T. Lasinski. A Tool for Visualizing the Topology of Three-Dimensional Vector Fields. in Visualization '91. 1991. Boston, Massachusetts: IEEE Computer Society Press.
- [10] Hin, A.J.S. and F.H. Post. Visualization of Turbulent Flow with Particles. in Visualization '93. 1993. Washington, D.C.: IEEE Computer Society Press.
- [11] Hultquist, J.P.M. Constructing Stream Surfaces in Steady 3D Vector Fields. in Visualization '92. 1992. Boston, Massachusetts: IEEE Computer Society Press.
- [12] Kenwright, D.N. and G.D. Mallinson. A 3-D Streamline Tracking Algorithm Using Dual Stream Functions. in Visualization '92. 1992. Boston, Massachusetts: IEEE Computer Society Press.
- [13] Leeuw, W.C.d. and J.J.v. Wijk. A Probe for Local Flow Field Visualization. in Visualization '93. 1993. Los Alamitos, CA: IEEE Computer Society Press.
- [14] Ma, K.-L. and P.J. Smith. Virtual Smoke: An Interactive 3D Flow Visualization Technique. in Visualization '92. 1992. Boston, Massachusetts: IEEE Computer Society Press.
- [15] Ma, K.-L. and P.J. Smith. Cloud Tracing in Convection-Diffusion Systems. in Visualization '93. 1993. Washington, D.C.: IEEE Computer Society Press.
- [16] Ma, K.-L. and Z.C. Zheng. 3D Visualization of Unsteady 2D Airplane Wake Vortices. in Visualization '94. 1994. Washington, D.C.: IEEE Computer Society Press.

Further Reading

- [23] Wijk, J.J.v., Flow Visualization with Surface Particles. IEEE Computer Graphics and Applications, July 1993. 13(4): p. 18-24.
- [24] Wijk, J.J.v. Implicit Stream Surfaces. in Visualization '93. October 1993. Los Alamitos, CA: IEEE Computer Society Press.
- [17] Max, N., B. Becker, and R. Crawfis. Flow Volumes for Interactive Vector Field Visualization. in Visualization '93. 1993. Los Alamitos, CA: IEEE Computer Society Press.
- [18] Max, N., R. Crawfis, and C. Grant. Visualizing 3D Velocity Fields Near Contour Surfaces. in Visualization '94. 1994. Washington, D.C.: IEEE Computer Society Press.
- [19] Max, N., R. Crawfis, and D. Williams, Visualization for Climate Modeling. Computer Graphics and Applications, 1993. 13(4): p. 34-40.
- [20] Pagendarm, H.-G. and B. Walter. Feature Detection from Vector Quantities in a Numerically Simulated Hypersonic Flow Field in Combination with Experimental Flow Visualization. in Visualization '94. 1994. Washington, D.C.: IEEE Computer Society Press.
- [21] Schroeder, W.J., C.R. Volpe, and W.E. Lorensen. The Stream Polygon: A Technique for 3D Vector Field Visualization. in Visualization '91. 1991. Boston, Massachusetts: IEEE Computer Society Press.
- [22] Wijk, J.J., van. Rendering Surface-Particles. in Visualization '92. 1992. Boston, Massachusetts: IEEE Computer Socie

Acknowledgements

- **Barry Becker and Nelson Max developed most of the software for the Flow Volumes.**
- **The Global Climate data is courtesy of the PCMDI program at LLNL.**
- **The NASA data sets are courtesy of David Lane, NASA Ames.**
- **The aerogel data is courtesy of Tony Ladd and Elaine Chandler.**
- **The HEPA filter data is courtesy of Bob Corey.**
- **The Groundwater data is courtesy of Steve Ashby.**
- **Funding for this research is through the LDRD program, LLNL.**